



T90-1 DK

Single Wing T 90 Fire Resistant Smoke Proof Ceiling Flap

Fire Protection T90 certified in accordance with DIN 4102 Smoke Control RS certified in accordance with DIN 18095

* Accessible * Stainless steel

Range of Dimensions: Width from 500 mm to 1100 mm Height from 500 mm to 1350 mm

* (possible special options)

Technical specification and text for invitation to tender

Product: T90-1 single wing fire resistant steel door brand Buchele

in accordance with DIN 4102

Door Type: T90-1 DK (System Schröders)

Dimensions: x mm

Door leaf: 67 mm thick, 4-sided folded finish, metall thickness 1,0 mm

Frame: 4-sided corner frame of 2,0 mm sheet metal with flush circumferential

Thelesol-fire protection bar. Rubber seal in fold.

Fitting: 2 pieces covered construction bands with ball bearing ring.

Top side with embedded shell handle

Bottom side with black fire protection handle on one side U-shape.

Self locking and opening aid via special opening aid

(max. opening angle $\leq 75^{\circ}$)

Surface: Door leaf and frame galvanized and primed with one component

primer similar RAL 7001

Installation: in concrete \geq 140 mm

Special Options

Accessible design: With aluminium corrugated sheet metal res. Grid

Stainless steel design: Material 1.4301 (V2A) res. 1.4571 (V4A),

Surface brushed and rotary matte finished



The Art of Doors

T90-1 DK







