

Single Wing Double Wall Steel Sliding Gate

- * Glazing
- * Ventilation Grille
- * Pedestrian Door
- * Stainless Steel

* (special options)

Product:	<u>DW 1-54 ST</u>
Dimensions:	up to 5000 x 5000 mm
Door leaf:	54 mm thick, of 1,5 res. 2,0 mm sheet metal edged (optional). Starting at 1,0 meter door width at least one butt seam in gate. With mineral wool filling. Edge overlap closing edge 50 mm. Opposite side 60 mm. lintel 70 mm.
Frame:	3-sided pressed maze sealing with 2 door guide shoes outside of door opening range.
Fitting:	With shell handle on side of intake. Outside a sturdy handle. The drive consists of 2 pieces double paired ball bearing rollers, running in a helmet rail. Ornamental bolt lock equipped for change to profile cylinder.
Surface:	Door leaf and frame galvanized and primed with one component primer similar RAL 7001

Special Options

Glazing:	Single res. insulated glazing optional. Minimum frieze width min. 125 mm circumferential. Selectively steel glass bar res. rubber clip profile.
Ventilation Grille:	Slanted segment standard in profile frame. Poke protected slanted double segments in profile frame.
Pedestrian Door:	Single wing pedestrian door with 4-sided frame circumferential. Mortice dead lock equipped for change to profile cylinder. Black door handle set in U-shape with short plate.
Stainless steel design:	Material 1.4301 (V2A) res. 1.4571 (V4A), Surface raw, brushed or rotary matte finished.

