

Double Wing Double Wall Steel Sliding Gate

- * Glazing
- * Ventilation Grille
- * Pedestrian Door
- * Stainless Steel

- * (special options)

Product:	<u>DW 2-54 ST</u>
Measuring range:	up to 10000 x 5000 mm
Door leaf:	54 mm thick, of 1,5 res. 2,0 mm sheet metal (optional) folded. From 1,0 meter door width at least one seam in door leaf surface. With mineral wool filling. Overlapping closing edge 50 mm. Opposite side 60 mm. Lintel 70 mm.
Frame:	3-sided pressed maze seal with 2 pieces door guide shoes beyond door opening range
Fitting:	Per wing on view side one shell handle. On outside solid handle. The running mechanism per wing consists of 2 double paired ball bearing rollers, running in a helmet rail. Ornamental bolt lock equipped for change to profile cylinder.
Surface:	Door leaf and frame galvanized and primed.
<u>Special Options</u>	
Glazing:	Single res. Insulated glazing optional. Minimum frieze width circumferential. 125 mm. Selectively with steel glass bar res. rubber clip profile.
Ventilation Grille:	Slanted segment standard. In profile frame. Pick safe slanted double segments in profile frame.
Pedestrian Door:	Single wing pedestrian door with 4-sided frame circumferential. Mortice dead lock equipped for change to profile cylinder. Black door handle set in U-shape with short plate, pre-punched for profile cylinder.
Stainless steel:	Material 1.4301 (V2A) res. 1.4571 (V4A), Surface brushed or rotary matte finished.

