

Steel Folding Sliding Gate FT

- * Glazing
- * Ventilation bar
- * Pedestrian door
- * Stainless steel

- * (special options)

Product: **FT3 – FT8**

Measuring range: optional

Door leaf: 55 mm thick, in smooth, 3-sided folded finish, of 2,0 mm sheet metal.
With mineral wool filling (selectively with PU foam filling).
Each door leaf with internal stabilizing ribs.
Wing base moulded as dripping edge.

Frame: 3-sided Z-casing 54/50/25/4 (selectively with 3-sided corner casing of 2,0 mm sheet metal with rubber seal in fold).
Separation rail as bottom junction profile.
With integrated top weather proof roof of 4,0 mm sheet metal.

Fitting: Per wing 3 pieces 3-parted construction bands with ball bearing ring.
To relieve stationary wing there is a double paired ball bearing roller running in helmet rail, opening angle 90 ° (selectively 180 °).
Movable wing with mortice dead lock equipped for change to profile cylinder.
Black door handle set U-shape with plate pre-punched for profile cylinder.
Each stationary wing with drive bolt and movable loop bolt on side.
Drive bolt made of flat iron, enforced at the ends.

Surface: Door leaf and frame galvanized and primed.

Special Options

Glazing: Single res. insulated glazing optional.
Minimum frieze width circumferential. 125 mm.
Selectively with steel glass bar res. rubber clip profile.

Ventilation Grille: Slanted segment standard. In profile frame.
Poke protected slanted double segments in profile frame.

Pedestrian Door: Single wing pedestrian door with 4-sided frame circumferential.
Mortice dead lock equipped for change to profile cylinder.
Black door handle set in U-shape with plate, pre-punched for profile cylinder.

Stainless steel: Material 1.4301 (V2A) res. 1.4571 (V4A),
Surface brushed or rotary matte finished.

Types of sill: Stopper with- res. without rubber seal.
4-sided Z- res. Corner frame.

