



The Art of Doors

Double wing Flood Protection Window

Water Tight up to 1,5 m WS (water column)

(Waterside is on side of hinges)

* Stainless steel

Range of Dimensions: Width from 1000 mm to 2500 mm

Height from 500 mm to 2250 mm

(* special options)

Technical specification and text for invitation to tender

Product: HF 50-2 double wing flood protection window brand Buchele

Window Type: HF 50-2

Water tight: up to 1,5 m WS (waterside is on side of hinges)

Dimensions: x mm

Frame: 4-sided thermally insulated block frame 87 mm thick, with 4-sided seal in

fold on the outside circumferential foaming agent in the center bar 110

mm wide

Window casement: 4-sided thermally insulated hollow sections with glass mounting nose on

one side and one side glass mounting frame 4 -sided visibly screwed to

the basic profile.

Fitting: per wing 3 pieces 3-parted adjustable hinges

per wing 1 piece 2 point locking with F1 anodized swivel handle additional tensioning handles (no. depending on size of window)

Glazing: Pressure resistant safety glazing installed in sealing bed

Surface: Frame and glass beads galvanized and primed with one component

primer similar RAL 7001

Mounting: Delivery and professional assembly.

Special Options

Stainless steel: Material 1.4301 (V2A) res. 1.4571 (V4A),

Surface raw, brushed and rotary matte finished.

Surface: Powder coated in RAL





HF 50-2

